

DeckHand *Portable Scale*



Scale
Only

Approvals



Measurement
Canada
Approved

Standard Features

- Mild or stainless steel wheeled frame, base, and mast
- Treaded top plate
- 500 lb, 1000 lb, 2000 lb capacity
- Standard indicator mount with integral handles for the IQ plus 355 IQ plus® 310A, IQ plus® 390-DC, IQ plus® 510, IQ plus® 590-DC, IQ plus® 710, IQ plus® 800 indicators, and IQ 700.
- Large rubber wheels simplify movement on uneven floors
- One-person portability
- RL1260 aluminum load cells

Specifications

DECKHAND PORTABLE SCALE

END LOAD CAPACITY:

100% end loading

mV/V OUTPUT:

2 mV/V

CABLE LENGTH:

9' 10" (3 m)

HEIGHT:

Weighing platter: 4.5" H when in weigh mode

COLUMN HEIGHT:

59"

APPROVALS:

NTEP - certified, CC# 98-004, Class III, 2500d;
Measurement Canada approved, AM-5218

WARRANTY:

1-year limited warranty

Please refer to indicator section for IQ plus 590-DC specifications

DeckHand *Rough-n-Ready System*



Scale
and
Indicator
Package

Approvals



Measurement
Canada
Approved

See page I-8 for Indicator specifications.

Standard Features

DeckHand Rough-n-Ready System

- Package includes: Mild steel DeckHand Portable Scale and IQ plus® 590-DC indicator
- Factory-wired and calibrated
- Treaded top plate
- Mild steel wheeled frame, base, and mast
- 500 lb, 1000 lb, 2000 lb capacity
- Large rubber wheels simplify movement on uneven floors
- One-person portability
- RL1260 aluminum load cells